

# 3MAX™ COMPOSITE REBAR

## PRODUCT TECHNICAL DATA



3MAX™ Composite Rebar is a high-strength composite reinforcing bar from MST-BAR®. Engineered for concrete flatwork, 3MAX™ Composite Rebar is made with code-compliant Vinyl Ester Resin & corrosion-proof ECR Glass Fibers to give your reinforced concrete centuries of serviceability.

 **3MAX™ Composite Rebar is an ASTM D7957 Certified Building Material.**

### ADVANTAGES

- **Rust-Proof**  
Completely eliminates cracks from spalling.
- **200+ Years Service Life**  
Engineered to last for generations.
- **Quick & Simple Installation**  
Save up to 50% labor compared to steel rebar.
- **Transportation Savings**  
75% lighter than traditional steel rebar.
- **High Performance in All Climates**  
Stronger reinforcement in freeze-thaw regions & guaranteed longevity in coastal regions compared to steel rebar.
- **Stronger Than Steel**  
Over 3X stronger than Grade 40 rebar.
- **Nonconductive & Nonferrous**  
Ideal for projects with electromagnetic sensitivity.
- **Superior Crack Control**  
80% less crack initiation compared to traditional steel rebar.
- **Chemical Resistant / No waterproofing**  
Impervious to de-icing salts and corrosive chemicals and eliminates the need for costly waterproofing agents.

### PHYSICAL & MECHANICAL PROPERTIES

<b>BAR DIMENSIONS</b>	0.375 in. Diameter
<b>CROSS-SECTIONAL AREA</b>	0.11 in. <sup>2</sup>
<b>BAR COMPOSITION</b>	Vinyl Ester Resin & ECR Glass Fiber
<b>BAR PROFILE</b>	Integral Rib Design (No Sand-Coating Required)
<b>TENSILE STRENGTH</b>	145 ksi (1000 MPa)
<b>ELASTIC MODULUS</b>	6675 ksi (46 GPa)
<b>SHEAR STRENGTH</b>	23.5 ksi (161 GPa)
<b>PULL-OUT CAPACITY</b>	2600 psi (18 MPa)

### APPLICATIONS

3MAX™ Composite Rebar replaces welded wire fabric/steel mesh and steel rebar for all (but not limited to) the following applications:

- Parking Lots
- Street Pavement
- Sidewalks
- Curb & Gutter
- Patios
- Decorative Concrete
- Slab on Grade
- Pool Decks
- Concrete Countertops

### HANDLING & INSTALLATION

Always wear gloves when handling 3MAX™ Composite Rebar to protect against fiberglass splinters. Avoid direct contact with skin. When cutting 3MAX™ Composite Rebar, use a diamond blade for best results. Tie and chair 3MAX™ Composite Rebar as you would steel rebar. Generally, minimum lap splice length of 15 inches is sufficient unless otherwise specified.

To learn more about 3MAX™ Composite Rebar and other MST-BAR® Composite Rebar Products, or to request pricing, give us a call or visit us on the web.

Give us a call at any of our branch locations, email us at [info@formtechinc.com](mailto:info@formtechinc.com), or click on [formtechinc.com/quote](http://formtechinc.com/quote) to get a quote. Our experienced Form Tech representatives will answer your questions, and help you get your project started with some of the best concrete forming, shoring, and accessory products in the industry, backed by a professional and detail-oriented staff.

---



### Charleston, SC

7377 Peppermill Lane  
North Charleston,  
SC 29418  
843.628.3434



### Detroit, MI

Corporate Headquarters  
975 Ladd Road  
Walled Lake,  
MI 48390  
Branch: 248.344.8260  
Corporate: 248.344.8265

---



### Charleston, WV

161 Industrial Road  
St. Albans,  
WV 25177  
304.722.6804



### Pittsburgh, PA

2850-A Kramer Road  
Gibsonia,  
PA 15044  
412.331.4500

---



### Charlotte, NC

1000 Thomasboro Road  
Charlotte,  
NC 28208  
704.395.9910



### Raleigh, NC

115 Peffinder Lane  
Raleigh,  
NC 27603  
919.833.0911

---



### Cleveland, OH

20801 Miles Road  
North Randall,  
OH 44128  
216.692.0497



TRUSTED FORMWORK & ACCESSORY SPECIALISTS

800-876-4857 | [info@formtechinc.com](mailto:info@formtechinc.com) | [formtechinc.com](http://formtechinc.com)