

FLEX-FORM® STEEL FORMING SYSTEM

CONCRETE CONSTRUCTION SOLUTIONS















System Features

The all-steel Flex-Form system gives you all the strength and versatility you expect from Symons. Flex-Form has integral 4" deep vertical stiffeners with 3/46" steel skin plate to provide up to a 1,200 psf system that adapts to any radius 5' and over.

Factory-rolled steel ribs set the radius and bolt to the top and bottom of flexible panels to shape and securely hold the form in the required radius. Panels conform accurately to the radius of the ribs — this design assures the correct radius every time. By substituting a straight rib, you can use the Flex-Form system for straight walls when needed.

Excellent Concrete Finish

Because the steel skin plate flexes to form the desired arc, there's no "chording" effect evident in the poured concrete surface. Conventional panel systems produce form joint marks that require grinding and rubbing, but the Flex-Form system produces smooth concrete surfaces that require practically no finishing labor.

Fast and Simple Erection

Panels are typically delivered to the jobsite pre-assembled to the required radius. There are no expensive templates to build, no floppy panels to handle and no bolts to torque. You can start building the Flex-Form gang immediately.

If the job requires more than one radius, simply order extra rolled ribs for use with the same forms. Changeover is simple, done quickly by the forming crew on the site. The new rolled ribs set the forms to the new radius, speeding the gang assembly and further increasing productivity.



Stacking Panels

Panels can be stacked by bolting the top and bottom ribs of the adjacent forms with the ³/₄" Speed Bolts and Nuts.

Void Panels

Rebar, pipe and other common form penetrations can be handled effectively with the interchangeable plywood-faced Void Panels.

Pour Door Panel

Concrete placement in large gangs can be controlled and consolidated by using the standard Pour Door Panel.

Walkway Brackets

Steel Walkway Brackets may also be bolted to the vertical stiffeners to provide workers safe access to the top of the forms.

Pipe Form Aligners

To provide vertical alignment, Pipe Form Aligners bolt directly to vertical stiffeners. Pipe Form Aligner have integral turnbuckles and telescoping extensions for lengths from 11'-1" to 20'-1".

Symons Soldier Beams

Available in 1'-6", 2', 3', 4', 8' and 12' lengths, Symons Soldier Beams can be used for alignment and bracing of Flex-Form gangs.

5" Steel Walers

Available in 4', 6', 8', 10', 12' and 16' lengths for vertical alignment and stability on extra high gangs.

50K She-Bolts or Taper Ties

High capacity ties provide maximum tie spacing to reduce gang setting and stripping time.

65K She-Bolts or Taper Ties

High Capacity ties with a SWL of 32,500lbs provide maximum tie spacing to reduce gang setting and stripping time. This system uses one-piece swivel wing nut that handle battered walls up to 10 degree without the use of special washers.

No Purchase Commitment

Every component in the Flex-Form forming system is rentable, including the fixed-radius ribs, ties and panels.











Give us a call at any of our branch locations, email us at info@formtechinc.com, or click on formtechinc.com/quote to get a quote. Our experienced Form Tech representatives will answer your questions, and help you get your project started with some of the best concrete forming, shoring, and accessory products in the industry, backed by a professional and detail-oriented staff.



Charleston, SC 7377 Peppermill Lane North Charleston, SC 29418 843.628.3434



Detroit, MI
Corporate Headquarters
975 Ladd Road
Walled Lake,
MI 48390
Branch: 248.344.8260

Corporate: 248.344.8265



Charleston, WV 161 Industrial Road St. Albans, WV 25177 304.722.6804



Pittsburgh, PA 2850-A Kramer Road Gibsonia, PA 15044 412.331.4500



Charlotte, NC 1000 Thomasboro Road Charlotte, NC 28208 704.395.9910



Raleigh, NC 115 Peffinder Lane Raleigh, NC 27603 919.833.0911



Cleveland, OH 20801 Miles Road North Randall, OH 44128 216.692.0497

